

6. ダクタイル鑄鉄異形管の管厚、外径、フランジ突部質量及び直部1m当たりの質量

単位 kg

呼び径	管厚 (mm)	外径 (mm)	フランジ突部								直部 1 m
			7.5K		10K		16K		20K		
			RF形	GF形	RF形	GF形	RF形	GF形	RF形	GF形	
T	D ₂										
75	8.5	93.0	3.77	3.66	2.28	2.17	3.00	2.89	3.29	3.18	16.134
100	8.5	118.0	4.55	4.40	2.75	2.61	3.98	3.84	4.33	4.18	20.907
150	9.0	169.0	6.22	6.02	5.59	5.39	7.73	7.53	8.90	8.70	32.346
200	11.0	220.0	8.06	7.80	6.75	6.49	9.89	9.63	11.2	11.0	51.641
250	12.0	271.6	11.5	11.1	10.7	10.4	16.5	16.2	19.6	19.3	69.975
300	12.5	322.8	14.2	13.8	11.4	11.0	19.7	19.3	23.1	22.7	87.126
350	13.0	374.0	18.8	18.3	13.4	12.9	26.0	25.6	30.0	29.5	105.416
400	14.0	425.6	21.8	21.3	19.4	18.9	36.0	35.5	42.8	42.3	129.437
450	14.5	476.8	28.3	27.7	24.7	24.1	47.3	46.7	55.5	54.9	150.573
500	15.0	528.0	32.0	31.4	28.3	27.6	56.3	55.7	65.4	64.8	172.848
600	16.0	630.8	38.9	38.2	39.0	38.3	75.0	74.2	86.1	85.3	220.958
700	17.0	733.0	49.9	49.1	52.1	51.3	98.2	97.4	143	142	273.412
800	18.0	836.0	66.1	65.1	67.7	66.7	132	131	213	212	330.736
900	19.0	939.0	85.3	84.3	80.3	79.2	156	155	256	255	392.643
1000	20.0	1041.0	101	98.2	100	97.2	207	204	—	—	458.682
1100	21.0	1144.0	120	116	122	119	237	234	—	—	529.730
1200	22.0	1246.0	140	136	152	148	287	283	—	—	604.867
1350	24.0	1400.0	181	177	194	190	369	365	—	—	741.798
1500	26.0	1554.0	216	212	239	235	451	446	—	—	892.386
1600	27.5	1650.0	275	264	295	284	—	—	—	—	1002.244
1650	28.0	1701.0	286	275	308	296	—	—	—	—	1052.228
1800	30.0	1848.0	318	306	358	345	—	—	—	—	1225.099
2000	32.0	2061.0	360	346	421	408	—	—	—	—	1458.438
2100	33.0	2164.0	386	372	461	447	—	—	—	—	1579.622
2200	34.0	2280.0	424	409	494	479	—	—	—	—	1715.318
2400	36.0	2458.0	538	522	651	634	—	—	—	—	1958.540
2600	37.5	2684.0	549	525	683	659	—	—	—	—	2229.252

編集注記 呼び径 50 は、定形寸法以外の製品に適用しないため記載していない。

資料